

# TELESCOPIC HOT STICKS



**CLOSE-UP: Universal Head with Disconnect Stick Adapter**

- Telescopic hot sticks offer long reach, speed, convenience and safety tested 100% per ASTM F-711. Fabricated of reinforced high density electrical grade fiber glass laminate for greater strength and dielectric properties. Cushioned cap protects base end.
- Triangle shape enables each section to “lock in automatically” eliminating twisting and turning to lock sections and provides an ergonomic design with a “better gripping” surface for better control.
- Fluorescent tip section is highly visible and has a foam core. All tip sections are 1.15” diameter.
- Larger share shape lock buttons are easy to operate with and without gloves.
- Versatility built in by using only the number of sections required. Tool height (length) can be reduced by depressing the lock button and sliding the bottom sections off. Allowing for a lightweight tool to perform the work easier.
- Easy disassembly by depressing the lock button and sliding a section, or sections, out without the use of additional tools.
- All sections have a smooth glossy surface for routing cleaning and waxing. Only one size lock button and spring for replacement needs.
- Universal head made of strong aluminum alloy incorporates corona discharge design holds universal attachments securely.
  - A complete line of tools and attachments for virtually any application, from pruning to cleaning to sawing, is available.

Telescoping Hot Sticks		
8' Extended Length: 1.75" Base Diameter (26" Retracted)	CPTS-208*	3 lbs
12' 7" Extended Length: 1.45" Base Diameter (58" Retracted)	CPTS-212	3.7 lbs
16' 9" Extended Length: 1.61" Base Diameter (60" Retracted)	CPTS-216	5.0 lbs
20' Extended Length: 1.75" Base Diameter (62" Retracted)	CPTS-220*	6.4 lbs
25' 6" Extended Length: 1.91" Base Diameter (64" Retracted)	CPTS-225*	8.1 lbs
30' Extended Length: 2.07" Base Diameter (66" Retracted)	CPTS-230	10.0 lbs
35' Extended Length: 2.22" Base Diameter (68" Retracted)	CPTS-235*	12.1 lbs
39' 6" Extended Length: 2.38" Base Diameter (69" Retracted)	CPTS-240*	14.4 lbs

Stick lengths beyond 8' require freight shipment/delivery.

*\*denotes special order item with approximate delivery of two weeks.*

***Cementex***

**The Safety Tool Specialists**