

Receptacle

Amperage	Lug I.D. Wiring Capacity			2P 50V	2P+15A Pilot 50V	2P+G+15A Pilot 690VAC/750VDC*	
	in	mm	AWG* mm ²				
75A	.23	6.0	6	16	5-2105-A	5-2106-A	5-2107-A
100A	.32	8.2	3	30	5-2105-B	5-2106-B	5-2107-B
125A	.36	9.2	1	40	5-2105-C	5-2106-C	5-2107-C
150A	.43	11.0	1/0	50	5-2105-D	5-2106-D	5-2107-D
200A	.50	12.5	2/0	75	5-2105-K	5-2106-K	5-2107-K

*May vary depending upon the type of wire used

Plug

Amperage	Lug I.D. Wiring Capacity			2P 50V	2P+15A Pilot 50V	2P+G+15A Pilot 690VAC/750VDC*	
	in	mm	AWG* mm ²				
75A	.23	6.0	6	16	5-0205-A	5-0206-A	5-0207-A
100A	.32	8.2	3	30	5-0205-B	5-0206-B	5-0207-B
125A	.36	9.2	1	40	5-0205-C	5-0206-C	5-0207-C
150A	.43	11.0	1/0	50	5-0205-D	5-0206-D	5-0207-D
200A	.50	12.5	2/0	75	5-0205-K	5-0206-K	5-0207-K

*May vary depending upon the type of wire used