

Solarod Overhead Heaters

Specifications

Model	Amps	K.W.	Voltage	Weight	Overall Length**	Replacement Elements
IPH512	4.10	0.5	120	3-1/4 LBS.	20-5/8"	EPH512
IPH1012	8.33	1.0	120	3-3/4 LBS.	25-1/8"	EPH1012
IPH1024	4.10	1.0	240	3-3/4 LBS.	25-1/8"	EPH1024
IPH1512	12.50	1.5	120	4-1/2 LBS.	34-5/8"	EPH1512
IPH1524	6.25	1.5	240	4-1/2 LBS.	34-5/8"	EPH1524
IPH1548	3.2	1.5	480	4-1/2 LBS.	39-5/8"	EPH1548
IPH2024	8.30	2.0	240	5-1/2 LBS.	44-5/8"	EPH2024
IPH2048	4.2	2.0	480	5-1/2 LBS.	44-5/8"	EPH2048
IPH2524	10.40	2.5	240	6-1/4 LBS.	51-5/8"	EPH2524
IPH2548	5.2	2.5	480	6-1/4 LBS.	51-5/8"	EPH2548

** Note: Subtract 3 5/8" from overall dimensions to establish distance between hangers.

Optional protective screens available:

KW	Screen Model
.5 KW	PWG-15
1.0 KW	PWG-20
1.5 KW	PWG-30
2.0 KW	PWG-20 (2 screens needed)
2.5 KW	PWG-15 (3 screens needed)

